LAMELLA: NATURAL



Light rustic quality with high percentage of lamellas of higher quality

- Knots till ± 60 mm.
- Black knots till ± 30 mm.
- Closed hearth is allowed.
- In bark till ± 100 mm is allowed.
- Rouge and wormholes are not allowed.
- A small line of sapwood of \pm 10 mm can occur on \pm 20% of the lamellas.





Frontside



Backside



Specifications

Thickness in mm

| | | 6,4 | 4,4 | 3,3 |
|--|--|-----|-----|-----|
|--|--|-----|-----|-----|

Width in mm

| 150 | 180 | 195 | 215 | 230 | 250 |
|-----|-----|-----|-----|-----|-----|
| | | | | | |

Length in mm

| 1250 | 1700 | 2000 | 2200 | 2500 |
|------|------|------|------|------|
| 2750 | 3000 | | | |

General information

All our lamellas are being produced in our up-to-date facility in Ukraine, which is provided of the latest "Neva" technology. This all makes us able to produce a very accurate end-product. After production our lamellas are being stored in our conditioned warehouse, where we take special measures (such as plastic wrapping and strengthening of the bundles) to secure all our products for shipment.

Thickness: The tolerance re

The tolerance regarding the thickness of our top layer production is \pm 0,2 mm, some pieces can be slightly thicker.

Quality: The quality of 10% of the lamellas can slight differ.